

SCHNELLVERSCHRAUBUNGEN –
MESSING, VERNICKELT

SCREW-IN FITTINGS - BRASS, NICKEL-COATED / RACCORDS RAPIDES - LAITON NICKELÉ

Material: Messing vernickelt
Medium: Druckluft, ungiftige Gase
Betriebstemperatur: -20°C bis +80°C
Betriebsdruck: max. 18 bar

Material: brass, nickel-coated
Media: compressed air; non-toxic gases
Operating temperature: -20°C to +80°C
Operating pressure: max. 18 bar

Matériau: laiton nickelé
Milieux: air comprimé, gaz non toxiques
Température de service: de -20°C à +80°C
Pression de service: max. 18 bar

PK		Gerade Einschraubverschraubung, Messing vernickelt					
		Straight screw-in fitting, brass nickel-coated / Raccord à visser droit, laiton nickelé					
Zylindrisches Außengewinde mit O-Ring NBR		G	Schlauch Hose / Tuyau Ø		SW [mm]	Mit O-Ring With O-ring Avec joint torique	Artikel-Nr. Item No. No. d'article
Cylindrical male thread with O-ring NBR			Da [mm]	Di [mm]			
Filetage extérieur cylindrique avec joint torique NBR		G1/8	6	4	13	Ja	80020101
			8	6	14	Ja	80020201
			10	8	14	Nein	80020202
		G1/4	6	4	16	Ja	80020301
			8	6	16	Ja	80020401
			10	8	16	Ja	80020501
		G3/8	6	4	19	Nein	80020502
			8	6	19	Ja	80020503
			10	8	19	Ja	80020504
			12	10	19	Ja	80020505
		G1/2	6	4	24	Ja	80020506
			8	6	24	Ja	80020507
			10	8	24	Ja	80020508
			12	10	24	Ja	80020509

PK

Winkel-Einschraubverschraubung, Messing vernickelt
Elbow screw-in fitting, brass nickel-coated / Raccord à visser coudé, laiton nickelé

Zylindrisches Außengewinde mit O-Ring NBR
Drehbar 360°

Cylindrical male thread with O-ring NBR
Rotatable 360°

Filetage extérieur cylindrique avec joint torique NBR
Pivotant à 360°



G	Schlauch Hose / Tuyau Ø		SW mm	Mit O-Ring With O-ring Avec joint torique	Artikel-Nr. Item No. No. d'article
	Da mm	Di mm			
G1/8	6	4	13	Ja	80020600
	8	6	13	Ja	80020700
G1/4	6	4	16	Ja	80020900
	8	6	16	Ja	80021000
	10	8	16	Ja	80021100

PK

T-Einschraubverschraubungen, Messing vernickelt

T-screw-in fitting, brass nickel-coated / Raccords à visser en T, laiton nickelé

Zylindrisches Außengewinde mit O-Ring NBR

Drehbar 360°

Cylindrical male thread with O-ring NBR

Rotatable 360°

Filetage extérieur cylindrique avec joint torique NBR

Pivotant à 360

G	Schlauch Hose / Tuyau Ø		SW mm	Mit O-Ring With O-ring Avec joint torique	Artikel-Nr. Item No. No. d'article
	Da mm	Di mm			
G1/8	6	4	13	Ja	80021200
	8	6	14	Ja	80021300
G1/4	6	4	16	Ja	80021500
	8	6	16	Ja	80021600
	10	8	16	Ja	80021700