

PK Y-Steckverbinder Y-push-in connector / Connecteur enfichable en Y							
3 Schlauch-anschlüsse 3 hose connections 3 raccords de tuyaux		Schlauch Hose / Tuyau Ø		Artikel-Nr. Item No. No. d'article	Schlauch Hose / Tuyau Ø		Artikel-Nr. Item No. No. d'article
		A 1x	B 2x		A 1x	B 2x	
		6	6	80041500	12	8	80042200
		8	6	80041900		10	80042300
			8	80041600		12	80041800
		10	6	80042000			
			8	80042100			
10	80041700						

PK

T-Steckverbinder

T-push-in connector / Connecteur enfichable en T

3 Schlauch-anschlüsse

3 hose connections

3 raccords de tuyaux

Schlauch Hose / Tuyau Ø		Artikel-Nr. Item No. No. d'article	Schlauch Hose / Tuyau Ø		Artikel-Nr. Item No. No. d'article
A 1x	B 2x		A 1x	B 2x	
6	6	80040500	10	10	80040700
	8	80041000		12	80041400
		10	80041100	12	12
8	8	80040600			
	10	80041200			
	12	80041300			

PK

X-Steckverbinder

X-push-in connector / Raccord enfichable en X

4 Schlauch-anschlüsse 4 hose connections 4 raccords de tuyaux		Schlauch Hose / Tuyau Ø		Artikel-Nr. Item No. No. d'article	Schlauch Hose / Tuyau Ø		Artikel-Nr. Item No. No. d'article
		A 2x	B 2x		A 2x	B 2x	
		6	6	80042400	10	10	80042600
			8	80043600		12	80044000
		8	8	80042500	12	12	80042700
			10	80043800			

SCHNELLVERSCHRAUBUNGEN –
MESSING, VERNICKELT

SCREW-IN FITTINGS - BRASS, NICKEL-COATED / RACCORDS RAPIDES - LAITON NICKELÉ

Material: Messing vernickelt
Medium: Druckluft, ungiftige Gase
Betriebstemperatur: -20°C bis +80°C
Betriebsdruck: max. 18 bar

Material: brass, nickel-coated
Media: compressed air; non-toxic gases
Operating temperature: -20°C to +80°C
Operating pressure: max. 18 bar

Matériau: laiton nickelé
Milieux: air comprimé, gaz non toxiques
Température de service: de -20°C à +80°C
Pression de service: max. 18 bar

PK		Gerade Einschraubverschraubung, Messing vernickelt						
		Straight screw-in fitting, brass nickel-coated / Raccord à visser droit, laiton nickelé						
Zylindrisches Außengewinde mit O-Ring NBR		G		Schlauch Hose / Tuyau Ø		SW [mm]	Mit O-Ring With O-ring Avec joint torique	Artikel-Nr. Item No. No. d'article
Cylindrical male thread with O-ring NBR				Da [mm]	Di [mm]			
Filetage extérieur cylindrique avec joint torique NBR		G1/8		6	4	13	Ja	80020101
				8	6	14	Ja	80020201
				10	8	14	Nein	80020202
		G1/4		6	4	16	Ja	80020301
				8	6	16	Ja	80020401
				10	8	16	Ja	80020501
		G3/8		6	4	19	Nein	80020502
				8	6	19	Ja	80020503
				10	8	19	Ja	80020504
				12	10	19	Ja	80020505
		G1/2		6	4	24	Ja	80020506
				8	6	24	Ja	80020507
				10	8	24	Ja	80020508
				12	10	24	Ja	80020509